

FEATURES & SPECIFICATIONS

POLE - The pole shaft is fabricated from hot rolled carbon steel having a minimum yield of 50,000 PSI and conforms to ASTM A500 grade C requirements. The shaft construction is a single piece of formed steel welded longitudinally. The hand hole is located 1' above the pole base. A ground lug is provided standard.

ANCHOR BASE — The anchor base is fabricated from a structural quality hot rolled carbon steel plate that has a minimum yield strength of 36,000 PSI. The anchor base telescopes the pole shaft and has a circumferential weld on the top and bottom.

BASE COVER — A full base cover is provided which encapsulates the base plate and anchor bolts to provide a clean transition from pier to pole.

FINISH — A Super Durable Polyester powder coat finish is electrostatically applied in our state of the art paint facility. Standard colors available: Black, Bronze, US Green, White. Custom colors available upon request. Galvanizing treatments available upon request. Additional warranty extensions available with these treatments

Technical Data

Nominal Pole Height	20'-0"
Shaft Dimensions	20' x 4"
Wall Gauge	11 Gauge
Bolt Circle	8.0"
Bolt Size	3/4" x 18" x 3"
Base Plate Dimensions	8.0" sq. x .75" thk.
Est. Shipping Weight	149 lbs

Max EPA (1.3 Gust)


SSP


SSP

KAB3418G08R

TLGFIA3


	· ,
90 mph	9.2
100 mph	6.6
110 mph	4.7
120 mph	3.2
130 mph	2.1
140 mph	1.2





8.0"

Pole Gauge




20' Steel 4" Square 11 Gauge Pole


SSP SERIES

T312

T238

T278





DM490

Drilling Locations

Sides	Α	В	С	D
Hand Hole	Х			
DM1	Х			
DM290	Х	Х		
DM2180		Х		Х
DM390	Х	Х		Χ
DM490	Х	Х	Х	Х

ORDERING INFORMATION

Pole Height

20 20' Nominal

Choose the bold face options for the appropriate pole configuration for your application and enter on the line above each pole attribute. Accessories may be factory installed, depending on the particular accessory chosen, but must

Pole Size

4 4" Square 11 Gauge **NOTE: ANCHOR BOLT KITS MUST BE ORDERED** AS A SEPARATE LINE ITEM. EACH KIT IS PROVIDED WITH A RIGID TEMPLATE FOR INSTALLATION. SEE ACCESSORIES FOR KIT PART NUMBERS. PLEASE NOTE ON PURCHASE ORDER IF ANCHOR BOLTS AND TEMPLATES ARE TO BE PRE-SHIPPED.

AB Kit (4) 3/4" x 18" Galvanized Bolts and Rigid

BK Black **BZ** Bronze WH White **GR** US Green **GLV** Galvanized GLVP¹ Galvanized and Painted SP Special

Color

Mounting DM1 Drill One Side **DM290** Drill 2 Sides at 90° **DM2180** Drill 2 Sides at 180° **DM390** Drill 3 Sides at 90° DM490 T238 T278

Example: SSP 20 4 11 BZ T238

Drill 4 Sides at 90° 2-3/8" OD Tenon (Standard) 2-7/8" OD Tenon 3-1/2" OD Tenon T312 ND No Drilling

Drill Pattern Blank None - for Tenon Mounting **SSA** SSA Drill Mount

Pattern **VSA** VSA Drill Mount Pattern KTN Drill Mount **KTN** Pattern

NOTES

- For 'Galvanized and Painted' option. You must specify a paint color code as the suffix in addition to the GLVP coating option. (Example: GLVPBZ).
- Please note location for additional hand hole when ordering. See Drilling Locations diagram for location designations.
- See Page 2 for details.
- Tenon tops T238, T278, and T312 are not available with the AVD option. If a tenon top is required with the AVD option, order the appropriate TVA for the application. For assistance, consult TL Sales.

Techlight 2707 Satsuma Drive, Dallas, TX 75229 PH: 214.350.0591 EMAIL: Techlight@techlight.com

Template

Accessories (Order as separate line items)

Ground Fault Receptacle

Additional Hand Hole

Poles Anti Vibration Device

PHH²


AVD203,4

SSP SERIES 20' Steel 4" Square 11 Gauge Pole


Accessories (Order as separate line items)

AVD20 - Anti vibration device for 20ft pole

PN#	Pole Height(ft)	CHAIN LENGTH (ft)
AVD20	30	13



TL-GFIA - Ground Fault Receptacle



The GFIA (Ground Fault Circuit Interrupter) comes with a die cast aluminum in-use cover.

For Refrence Only: The ASCE 7 Hazard Tool is the official source of information for pole selection when identifying wind speed zone limits within North America.

https://ascehazardtool.org/