

FEATURES & SPECIFICATIONS

POLE — The pole shaft is fabricated from hot rolled carbon steel having a minimum yield of 55,000 PSI and conforms to ASTM A572 Grade 55 or A595 Grade A requirements. The shaft construction is a single piece of formed steel welded longitudinally. The hand hole is located 1' above the pole base. A ground lug is provided standard.

ANCHOR BASE — The anchor base is fabricated from a structural quality hot rolled carbon steel plate that has a minimum yield strength of 36,000 PSI. The anchor base telescopes the pole shaft and has a circumferential weld on the top and bottom.

BASE COVER — A full base cover is provided which encapsulates the base plate and anchor bolts to provide a clean transition from pier to pole.


FINISH — A Super Durable Polyester powder coat finish is electrostatically applied in our state of the art paint facility. Standard colors available: Black, Bronze, US Green, White. Custom colors available upon request. Galvanizing treatments available upon request. Additional warranty extensions available with these treatments.


Technical Data

Nominal Pole Height	39'-0"
Shaft Dimensions	Base OD 7.13" Top OD 2.87"
Wall Gauge	7 Gauge
Bolt Circle	13.5"
Bolt Size	1" x 36" x 4"
Base Plate Dimensions	13.0" sq. x 1.0" thk.
Est. Shipping Weight	500 lbs

Max EPA (1.3 Gust)

90 mph	14.2
100 mph	10.4
110 mph	7.5









39' Steel Square Tapered 7 Gauge Pole

STP SERIES

Mounting Options





Drilling Locations

Example: STP 39 7.13 7 BZ T238

Sides	Α	В	С	D
Hand Hole	Х			
DM1	Χ			
DM290	Χ	Χ		
DM2180		Х		Χ
DM390	Х	Х		Х
DM490	Х	Х	Х	Х

ORDERING INFORMATION

Choose the bold face options for the appropriate pole configuration for your application and enter on the line above each pole attribute. Accessories may be factory installed, depending on the particular accessory chosen, but must still be ordered as a separate line item.

STP **Pole Height Pole Shaft Base Pole Gauge** Color Mounting **Drill Pattern** STP **7** 7 Gauge DM1 **39** 39' Nominal **7.13** 7.13" OD **BK** Black Drill One Side Blank None - for Tenon **BZ** Bronze **DM290** Drill 2 Sides at 90° Mounting WH White DM2180 Drill 2 Sides at 180° **SSA** SSA Drill Mount **GR** US Green DM390 Drill 3 Sides at 90° Pattern **GLV** Galvanized **DM490** Drill 4 Sides at 90° VSA Drill Mount GLVP¹ Galvanized and Painted 2-3/8" OD Tenon (Standard) T238 Pattern T278 2-7/8" OD Tenon KTN Drill Mount SP Special **KTN** T312 3-1/2" OD Tenon Pattern ND No Drilling

NOTE: ANCHOR BOLT KITS MUST BE ORDERED AS A SEPARATE LINE ITEM. EACH KIT IS PROVIDED WITH A RIGID TEMPLATE FOR INSTALLATION. SEE ACCESSORIES FOR KIT PART NUMBERS. PLEASE NOTE ON PURCHASE ORDER IF ANCHOR BOLTS AND TEMPLATES ARE TO BE PRE-SHIPPED.

NOTES Accessories (Order as separate line items) 1 For 'Galvanized and Painted' option. You must specify a paint color code as the suffix in addition to the GLVP coating option. (Example: GLVPBZ). KAB136G135R AB Kit (4) 1" x 36" Galvanized Bolts and Rigid PHH² Additional Hand Hole Please note location for additional hand hole when ordering. See Drilling Locations Template AVD393 Poles Anti Vibration Device diagram for location designations. TLGFIA3 Ground Fault Receptacle 3 See Page 2 for details.


Techlight
2707 Satsuma Drive, Dallas, TX 75229
PH: 214.350.0591 EMAIL: Techlight@techlight.com

STP SERIES 39' Steel Square Tapered 7 Gauge Pole


Accessories (Order as separate line items)

AVD39 - Anti vibration device for 39ft pole

PN#	Pole Height(ft)	CHAIN LENGTH (ft)
AVD39	39	26



TL-GFIA - Ground Fault Receptacle



The GFIA (Ground Fault Circuit Interrupter) comes with a die cast aluminum in-use cover.

For Refrence Only: The ASCE 7 Hazard Tool is the official source of information for pole selection when identifying wind speed zone limits within North America.

https://asce7hazardtool.online/