

SPECIFICATION SHEET

SEBCO 900-1200



FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- SOME 120 VOLT TRANSFORMERS AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS. 230 VAC TRANSFORMERS MEET *CE* REQUIREMENTS

REQUIREMENTS

• LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838



- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

PART NUMBER PRIMARY VOLTAGE OUTPUT VOLTAGE BREAKERS FREQUENCY DIMENSIONS WEIGHT

CLASS 1 1103-24 (900 Watt) 120VAC-8.25A MAX 24VAC-38A MAX 2x20A

60 Hz

10.25" x 5.625" x 5.25" 28 LBS.

CLASS 1

1027-24 (1000 Watt) 120VAC-10A MAX 24VAC-42A MAX 2x25A 60 Hz 10.25" x 5.625" x 5.25" 28 LBS.

CLASS 1

1028-24 (1200 WATT) 120VAC-11A MAX 24VAC-50A MAX 2X25A 60 Hz 10.25" x 5.625" x 5.25" 28 LBS.