ACCESSORIES FA-BQCOVER

> 5 127n

BQ-FC01 Cut Sheet 112018

BARBECUE LIGHTS: THREADED EGG BQ-FC01 CLAMP SERIES

SPECIFICATIONS

CONSTRUCTION: 316 stainless steel housing ARM: 12" tall 316 stainless steel rigid stem with a 16" stainless steel flex arm on top and clear weatherproof polyolefin cover over flex arm MOUNT: 3" (max opening 2") or 5" (max opening 3.5") stainless steel clamp FINISH: Stainless Steel - Brushed LENS: High impact clear tempered flat glass O-RING: High temperature red silicone, 70 durometer SWITCH: On/Off push button with weatherproof rubber boot cover

12v ELECTRICAL SPECIFICATIONS:

LED SUPPLIED: 7w MR16 GU5.3 Super Saver (L-48) 40,000 hours average rating SOCKET: High temperature ceramic GU5.3 bi-pin, 250°C silicone insulated lead wires WIRING: Black 10 foot 18/2 zip cord from base of fixture (12v only) For 25 foot 16/2 wire add-25F to catalog number

120v ELECTRICAL SPECIFICATIONS:

LED SUPPLIED: 7w ARROW PAR16 (L-134) 40,000 hours average rating SOCKET: High temperature ceramic Base (E26/27) medium base, 250°C silicone insulated lead wires WIRING: 120 volt supplied with 9 foot power cord & plug.

16"

406mm


12" 305mm

ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT
12v			
BQFC301L48SS	3" Clamp Mount BBQ Light	7w MR16 LED SS	4.0 lbs.
BQFC501L48SS	5" Clamp Mount BBQ Light	7w MR16 LED SS	4.0 lbs.
120v			
BQFC301L134SS	3" Clamp Mount BBQ Light	7w PAR16 LED SS	4.0 lbs.
BQFC501L134SS	5" Clamp Mount BBQ Light	7w PAR16 LED SS	4.0 lbs.
	1 5		

Vinyl Protective Cover For Flex-Arm BQ Lights w/ Drawstring Closure







ΎΡΕ