



SPECIFICATION SHEET



FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- INPUT VOLTAGE OF 277 VAC. OUTPUT VOLTAGE OF 115 VAC.
- UL INSULATION SYSTEM E86543-CLASS F 155°C
- CONSERVATIVE HEAT RISE CHARACTERISTICS
- BI-DIRECTIONAL DESIGN FOR STEP-UP OR STEP-DOWN USE
- 50, 100 AND 250 WATT OPTIONS AVAILABLE

REQUIREMENTS



- UL LISTED TRANSFORMER.
 - ANSI/UL506
 - ANSI/UL5085-1
 - ANSI/UL5085-2
- RoHS AND REACH COMPLIANT

	50 WATT	100 WATT	250 WATT
SEBCO PART NUMBER	MC-50	MC-100	MC-250
UL P/N	4-56-0050	4-56-0100	4-56-0250
PRIMARY VOLTAGE	277 VAC	277 VAC	277 VAC
OUTPUT VOLTAGE	115 VAC	115 VAC	115 VAC
FREQUENCY	50/60 Hz	50/60 Hz	50/60 Hz
DIMENSIONS	2.30" X 2.0" X 1.98"	2.4" x 2.25" x 2.3"	3.50" x 3.00" x 3.25"
WEIGHT	1.5 LBS.	1.65 LBS	3.85 LBS